



ADHERE BONDS
The Versatile Construction Chemicals

ADHERE FIX - 520

Tile Adhesive for BADA

DESCRIPTION:

Adherefix 520 Tile Adhesive is an acrylic based polymer. It makes indoor & outdoor non-concrete tile installations possible such as tile-over-tile, tiling on wood, metal, fiber cement board and marble & granolithic flooring. **Adherefix 520** adds flexibility without compromising the adhesive's bonding strength.

ADVANTAGE:

- Extra Strong
- Extra Flexible
- High Shear Strength
- Thermal Deformability
- Tiling on Non-concrete substrates
- Enhance Impact Resistance
- Excellent Water Resistance
- Excellent Heat Resistance
- Quick Drying Time.

SURFACE PREPARATION:

The surface must be fully cured, structurally stable, level, even, clean and free from contaminants such as dirt, dust, loose material, oils and chemicals. The use of a level bar is essential to ensure levelness and / or plumpness of the surface. For painted surfaces, acid etch or abrade paint to ensure proper bonding.

APPLICATION GUIDE:

- Make sure the surface of the tile is clean and free of dust apply ADHERE FIX 502 Back of tile by roller or brush directly to the back of tiles consumption 100-150 rms /m² wait until it is touch dry 30 mints@room temperature slightly tacky finally attach the tile on surface of the wall's on adhesive firmly.
-

Note:

Whilst any information and / or specification contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendation or suggestions made by us, our representatives, agents or distributors as the conditions of use of any labour involved are beyond our control.

Coverage: 100-150gm /m²

PACKAGING: 0.5kg, 1kg, 5kg

STORAGE & SHELF LIFE

When stored in a cool dry place & in its original unopened packaging, **Adherefix 520** Tile Adhesive Additive will remain usable one year from date of manufacture.

Adhere Bonds
Coats Pvt Ltd

